

CAR MIRROR

PRODUCT DESCRIPTION

Adhesive For rear view mirrors.

FIELD OF APPLICATION

For fixing a rear view mirror to a windscreen.

PROPERTIES

Dilutability: the adhesive cannot be diluted.

Temp. resistance: from -40°C up to +90° C

Resistance to moisture: waterproof.

Chemical resistance: good.

Ageing resistance: good.

TECHNICAL DATA

Basic material	: methacrylic ester.
Colour	: transparent.
Solids content	: 100 %.
Specific gravity	: 1090 kg/m ³ .
Viscosity	: 5 - 7 Pa.s. at +20°C.
Flash point	: —

APPLICATION

Surface treatment: The surfaces (windscreen and metal mirror base) must be clean, dry and grease-free. Clean off any remains of previous adhesive. Mark the position of the rear view mirror base on to the windscreen. Trim mesh to the size and shape of the mirror base. Apply a thin coat of adhesive from the syringe to the mirror base. Spread evenly to cover area. Place the mesh over the adhesive and apply immediately to the windscreen. Hold firmly in place for at least one minute and then do not disturb for a further 15 minutes.

Application temp.: Do not apply below +10° C.

Setting time: Full setting after approx 24 hours.

Important: Close properly after use and store in a cool, dark, fros-free place.


STAINS

Remove stains immediately with acetone.

STORAGE PROPERTIES

Bison Car Mirror has a shelf life of about 18 months, provided it is stored unopened in a cool, dry and dark place.

WARNING

Symbol	= Xi.	
R 36/37/38	= Irritating to eyes, respiratory system and skin.	
R 43	= May cause sensitization by skin contact.	
S 2	= Keep out of reach of children.	
S 24	= Avoid contact with skin.	
S 26	= In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.	
S 51	= Use only in well ventilated areas.	

TRANSPORT CLASSIFICATIONS

Not applicable.

01; 001009

Our instructions are based on extensive investigations and experience. In view of the large variety of materials and the conditions under which our products are applied, no responsibility can be assumed for the results obtained and/or any damage caused from the use of the product. However, our Service Department is quite willing to supply any advice needed.

Head office: Bison International - P.O. Box 160, 4460 AD Goes (NL). Tel. 31-113-248248, Fax 31-113-232077, e-mail: info@bison.boltongroup.nl